



# Cool FOCS 1902 SL 352 kW Chiller

EUROVENT  
certified



## Technical Specifications

Dimensions (L x W x H)	3.150 x 2.400 x 2.450 mm
Weight	3.930 kg
Water Connections	4" Bauer Quick Release
Nom. Cooling Capacity	352 kW at 7/12°C and 32°C Ambient
Compressor	2 x Bitzer Screw
Refrigeration Circuits	2
Refrigerant	R 134a
Nom. Water Flow	61 m <sup>3</sup> /h
Delta T min / max	3 – 8 K
Max. Working Pressure	6 bar
Electr. Power Absorbed	179 kW
Power Supply	400 V / 50 Hz / 3 Ph
Max. Running Current	292 amp
Power Connections	12 mm LUGS
Sound Pressure Level	54 dB(A) / 10 m free field

Wird das Gerät an einem Fehlerstromschutzschalter (FI) betrieben, ist ein allstromsensitiver FI Typ B zu verwenden / If a Residual Current Device (RCD) is used, it has to be RCD type B (AC-DC sensitive)

Herstellerangaben. Technische Änderungen vorbehalten / Abb. ähnlich  
Manufacturers data. Specifications subject to change without notice / fig. similar

## Features

This fully packaged chiller contains the latest energy-saving semi-hermetic Bitzer Screw compressors, with an array of 2 serviced on 2 independent refrigeration circuits. The chiller is fully Eurovent compliant and offers the latest HFC R 134a. With 4" quick-release water and power connections, Cool FOCS 1902 SL has been designed for a fast rental installation and start up.

The chiller can be supplied with an atmospheric or pressured set-up and can manage a wide range of temperature requirements (-10 to +20°C).

## Benefits

The 352 kW rental chiller has been designed to offer a low-noise option to the HVAC and process cooling market. This lightweight unit has the smallest footprint/kW rating currently on the rental market.

In addition to this, CoolEnergy is committed to reducing carbon emissions throughout the industry. Our 352 kW rental chiller is currently rated Class A in energy efficiency by Eurovent meaning that your electricity usage will be lower by using this CoolEnergy unit. We can also provide connecting pipework & tanks.

For example  
compatible with  
Air Handling unit  
Cool AIR 350 F

